




professional control devices

ClimateController

Vers. 01-21



Available in:



7AMP



12AMP



16AMP

ADVANCED CLIMATE SOLUTIONS



www.cli-mate.pro

Control your environment



Serie: KC
 Type: KC2010-T7 / KC2010-T12 /
 KC2010-T16

ClimateController

Vers. 01-21

TEMPERATURE, MIN., MAX. SPEED & HYSTERESIS ADJUSTMENT

Automatic - Professional

- Fully adjustable, automatic temperature control
- 2 Fan inlets on the sides of the device
- Advanced hysteresis fan speed adjustment with 7°C of bandwidth
- Easy to calibrate using knobs
- Includes a mounting plate on the back side
- Incorporates a sensor for the indoor temperature

Automatic, two inlets for fans

Hysteresis range of up to 7°C

Controls indoor temperature

Technical data

Temperature range	: 5 - 55 °C
Power supply	: 220/230V – 50Hz
Switching differential	: 1°C per step (hysteresis)
Protection class	: IP44
Measures	: 220 x 140 x 110 mm



A = Set the desired temperature
 B = Set the bandwidth (hysteresis)


C = Min. Fan Speed %
 D = Max. Fan Speed %

NOTE: **NEVER** surpass the maximum charge recommended! (AC motors)



The design and the writing of this leaflet have been realized with the most thorough accuracy. We do not take responsibility for printing or typing mistakes.

www.cli-mate.pro

 Fan (min., max. speed)  °C Temperature  Fuse  Bandwidth